



Technical Data Sheet

UCARE™ JR-30MP Polymer

Conditioning Polymer

INCI Name: Polyquaternium-10

Features & Benefits

- Substantive to hair and skin
- Medium to strong conditioning
- Enables deposition of silicone
- Minimal build-up on hair, volume friendly
- Hair repair
- Split end mending from anionic and amphoteric shampoo systems
- Can be formulated into clear shampoo systems
- Can be formulated into opacified shampoo systems

Applications

UCARE™ polymers are used in a diverse number of applications across both hair and skin care. Perhaps the most notable for the UCARE™ JR-30MP Polymer is its ability to provide substantive conditioning from shampoo systems.

Typical Properties

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result
Viscosity, 1% Aqueous Solution	cP	1000–2500
Volatiles	Wt%	6.0 Max
Nitrogen	Wt%	1.70–2.20
Ash	Wt%	0–3

Description

UCARE™ polymers are polymeric, quaternary ammonium salts of hydroxyethylcellulose reacted with trimethyl ammonium substituted epoxide. The cellulosic backbone is derived from natural, renewable resources.

UCARE™ polymers are generally grouped into three categories. The LK grade has the lowest level of % Nitrogen (0.4-0.6), followed by the LR grade (0.8-1.1), and finally the JR grade (1.5-2.2). Increasing the amount of nitrogen substitution provides more substantive bonding to the hair surface and a smoother film microtexture.

UNRESTRICTED – May be shared with anyone

™Trademark of The Dow Chemical Company ("Dow") or an affiliated company of Dow

UCARE™ JR-30MP Polymer

© 2018 The Dow Chemical Company. All rights reserved.




Figure 1: The Idealized Structure of UCARE Polymers

Recommended
Use Level

Recommended Applications

Shampoo Systems, body wash, creams and lotions, hair styling products:

- 0.2–0.5 wt%

Methods of
Addition

There are two basic methods for preparing UCARE™ Polymers for incorporation into your formulation.

I. Prior Polymer Hydration

- Hydration of the polymer is accomplished by slowly adding the dry powder into agitated room temperature water and allowing it to mix until the solution is uniform and clear.
- Hydration can be accelerated by heating the solution to 65°C. Once the polymer is fully hydrated, simply add the solution directly to the surfactant system blend with mixing.
- Hydration may be accomplished separately or as a first step in the manufacturing procedure.

II. Addition with Co-Solvents

- A slurry of the dry powder may be made in a non-aqueous, water soluble, co-solvent (such as propylene glycol, glycerin, low molecular weight CARBOWAX™ Polyethylene Glycols, or Methyl Gluceth-10 or -20).
- The slurry can then be mixed into the water or directly into the surfactant blend.
- Hydration can be accelerated by heating the solution to 65°C.
- The co-solvent "wets" the polymer and allows it to be more easily dispersed, thus increasing the rate of hydration whether it is in the water or directly put into the surfactant blend.

Handling
Precautions

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.

Usable Life and
Storage

Store in a dry place. Protect from atmospheric moisture. Avoid prolonged exposure to heat and air.

Limitations

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

Health And
Environmental
Information

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, consumer.dow.com or consult your local Dow representative.

consumer.dow.com

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

