

Beeswax Blend 164

Product type

Beeswax Blend 164 is a blend of beeswax with other ingredients.

: Paraffin; Glyceryl palmitate/stearate; Cera alba; Stearic acid.

CAS : 8002-74-2; 68002-71-1; 8012-89-3; 57-11-4.

Applications / Properties

Beeswax Blend 164 is a blend of beeswax with other ingredients. In this partially synthetic beeswax the chemical, physical and performance characteristics are comparable with pure beeswax.

Product characteristics

Technical Data	Specification	Typical	Method
Colour		Off white	Visual
Colour Lovibond yellow	Max. 10		-
Colour Lovibond red	Max. 1.5		-
Congealing point	61 - 65 °C		ASTM D 938
Drop melting point	61 - 65 °C		ASTM D 3954
Ester value	70 - 80 mg/g		-
Acid value	17 - 24 mg/g		ASTM D 1386
Saponification value	87 - 104 mg/g		ASTM D 1387

Application systems

Creams and ointments Decorative cosmetics Stick form products

Storage

Beeswax Blend 164 has a shelf life of at least two years (from production date) when stored under cover in cool, dry conditions. Stock rotation should be practised.

Disclaimer

Information and details given in this document, particularly any recommendations for application and use of our products are based on careful laboratory tests and prevailing practical experience and are believed to be correct at time of publication. The information is not binding, which is also generally true for our practical customer service, given verbally, in writing and by tests. Due to (possibly varying) conditions of transport, storage, process, substrate use or product application (which are beyond our knowledge and control), we strongly recommend to carry out sufficient tests in order to ensure that our products are suitable for the intended processes and applications. Further, it is the user's obligation to utilize this material with due care, in accordance with the information in the Material Safety Datasheet (and with the information given in any other way by Paramelt') and in full compliance with health, safety and environmental regulations. Whilst proper care has been taken in the preparation of this Odocument, no liability for damage or injury resulting from its use is accepted, other than the limited liability which may arise towards a contractual party on the basis of Paramelt's conditions of sale (a copy of these conditions is available on request). Paramelt's acceptance of any orders for this product is expressly conditional upon purchaser's assent to these conditions of sale. No information contained in this document (nor any information given verbally, in writing and by tests) is to be construed as permission, recommendation or inducement by Paramelt or its officers, employees or affiliates, to use any product or process so as to infringe upon or conflict with any patent. Paramelt does not attest or guarantee that the use of its products or processes will not infringe upon any patent; user is responsible for verifying its freedom to operate in any jurisdiction

Version: 2018/05 | Spv: 14 | Page 1 of 1